

INDUSTRIAL ETHERNET WORKGROUP SWITCH

24 Port Fast/Gigabit Ethernet Workgroup Switch MACH104-20TX-FR



Product Description	
Description	24 ports Gigabit Ethernet Industrial Workgroup Switch (20 x GE TX ports, 4 x GE SFP combo Ports), managed, Software Layer 2 Professional, Store-and-Forward-Switching, fanless design
Port type and quantity	24 ports in total; 20x (10/100/1000 BASE-TX, RJ45) and 4 Gigabit Combo Ports (10/100/1000 BASE-TX, RJ45 or 100/1000 BASE-FX, SFP)
Type	MACH104-20TX-FR
Order No.	942 003-101
More Interfaces	
Power supply/signaling contact	1 x plug-in terminal block, 2-pin, output manual or automatic switchable (max. 1 A, 24 V DC bzw. 24 V AC)
V.24 interface	1 x RJ11 socket, serial interface for device configuration
USB interface	1 x USB to connect the AutoConfiguration Adapter ACA21-USB
Network Size - Length of Cable	
Twisted pair (TP)	0 m
Multimode fiber (MM) 50/125 µm	see SFP LWL-Module M-FAST SFP-MM/LC and SFP LWL-Module M-SFP-SX/LC
Multimode fiber (MM) 62.5/125 µm	see SFP LWL-Module M-FAST SFP-MM/LC and SFP LWL-Module M-SFP-SX/LC
Single mode fiber (SM) 9/125 µm	see SFP LWL-Module M-FAST SFP-SM/LC und SFP LWL-Module M-SFP-LX/LC
Single mode fiber (LH) 9/125 µm (long haul transceiver)	see SFP LWL-Module M-FAST SFP-SM+/LC
Network Size - Cascadability	
Line - / star topology	any
Ring structure (HIPER-Ring) quantity switches	50 (reconfiguration time < 0.3 sec.)
Power Requirements	
Operating voltage	100-240 VAC, 47-63 Hz
Heat dissipation	119 Btu (IT) h
Rated current	n/a
Power consumption	35 W
Software	
Management	serial interface, Web-Interface, SNMP V1/V2, HiVision File transfer SW HTTP/TFTP
Diagnostics	LEDs, Log-File, Syslog, signal contact, RMON (Statistic, History, Alarms, Events), Port mirroring, Topology Discovery 802.1AB, Cable tester
Configuration	Command Line Interface (CLI), TELNET, BootP, DHCP, DHCP Option 82, HiDiscovery, AutoConfiguration Adapter (ACA11, ACA21-USB), Watchdog Configuration, integrated DHCP server
Security	Port Security (IP und MAC), SNMP V3, SSH, Authentication (802.1x)
Redundancy functions	HIPER-ring (Ring structure), MRP (IEC-Ring function), RSTP 802.1D-2004, redundant Net/Ring coupling, Dual Homing, Link Aggregation
Filter	n/a
Industrial Profiles	n/a
Realtime	n/a
Flow control	n/a
Ambient Conditions	
Operating temperature	0 °C - 50 °C
Storage/transport temperature	-20 °C - 85 °C
Relative humidity (non-condensing)	10 % - 95 %
MTBF	n/a
Mechanical Construction	
Dimensions (W x H x D)	448 mm x 44 mm x 345 mm
Mounting	19" control cabinet
Weight	4400 Gram
Protection class	IP20



INDUSTRIAL ETHERNET WORKGROUP SWITCH

Mechanical Stability	
IEC 60068-2-27 shock	15 g, 11 ms duration, 18 shocks
IEC 60068-2-6 vibration	3.5 mm, 5–8.4 Hz, 10 cycles, 1 octave/min; 1 g, 8.4–150 Hz, 10 cycles, 1 octave/min
EMC Interference Immunity	
EN 61000-4-2 electrostatic discharge (ESD)	4 kV contact discharge, 8 kV air discharge
EN 61000-4-3 electromagnetic field	10 V/m (80-3000 MHz)
EN 61000-4-4 fast transients (burst)	2 kV power line, 4 kV data line
EN 61000-4-5 surge voltage	power line: 2 kV (line/earth), 1 kV (line/line), 4 kV data line
EN 61000-4-6 conducted immunity	10 V (150 kHz-80 MHz)
EMC Emitted Immunity	
FCC CFR47 Part 15	FCC 47 CFR Part 15 Class A
EN 55022	EN 55022 Class A
Approvals	
Safety of industrial control equipment	cUL 508 (pending)
Safety of information technology equipment	cUL 60950-1 (pending)
Scope of Delivery and Accessories	
Scope of delivery	MACH100 device, terminal block for signal contact, 2 brackets with fastening screws (pre-assembled), housing feet - stick-on, non-heating appliance cable - Euro model, CD-ROM with user manual, installation user manual
Accessories to order separately	Fast Ethernet SFP modules, Gigabit Ethernet SFP modules, auto Configuration Adapter ACA21-USB, terminal cable, Industrial Hivision Network Management software

